



Subcategory

Multi-Vapor Metal Halide Lamps

| | |
|---|-----------------|
| <u>Product Code</u> | 41826 |
| <u>Description</u> | MVR1000/U |
| <u>Watts</u> | 1000 |
| <u>Lumens (Initial)</u> | 108000V/100280H |
| <u>Lumens (Mean)</u> | 86000V/79000H |
| <u>Average Life in Hours</u> | 11000H/15000V |
| <u>Color Temperature (K)</u> | 4000 |
| <u>Color Rendering Index (Ra) CRI (> or =)</u> | 65 |
| <u>Operating Position Code</u> | U |
| <u>Fixture Type - Open/Enclosed</u> | S |
| <u>Bulb Type</u> | BT56 |
| <u>Base Type</u> | Mog |
| <u>Max Overall Length (In.)</u> | 15.37 |
| <u>Max Overall Length (mm)</u> | 391 |

| | |
|---------------------------------|--|
| <u>LCL (In.)</u> | 9.5 |
| <u>ANSI Ballast Type</u> | M47 |
| <u>Sales Unit UPC</u> | 043168418263 |
| <u>Case UPC</u> | 043168418263 |
| <u>SCC</u> | 00043168418263 |
| <u>Govt. Nat'l Stock Number</u> | 6240010120829 |
| <u>Case Quantity</u> | 6 |
| <u>Additional Information</u> | Clear |
| <u>Footnotes</u> | Not for use with lampholders that have stainless steel center contacts to avoid lamp or lampholder damage due to arcing. |